

SDLink2/AU

Single Channel KVM Extender Kit

All you need to extend one channel of high-resolution video, PS/2 keyboard and mouse, stereo audio, and serial port signals up to 300m over Category 5, 5e, 6 or Level 7 (CATx) cable.

- **High video resolution:**
1600x1200@60Hz up to 65m
1280x1024@75Hz up to 120m
1024x768@75Hz up to 300m
- **Transparent serial port**
- **Bi-directional stereo audio**
- **Dual Access with Private mode**
- **Fully adjustable video equalization**
- **DDC emulation**
- **Surge-protected CATx interfaces**
- **Keyboard and mouse emulation ensures CPU boots under all circumstances**
- **Local units powered directly by PC**
- **Shielded steel chassis**
- **Rack mount kit available**



Remote unit - front view

Contents

- Extender Remote unit
- 9V DC universal power supply for Remote unit
- Extender Local unit
- KVM CPU cable set (1.8m) with PS/2 keyboard and mouse connectors, and VGA video connectors
- Serial cable (1.8m)
- Dual audio cables (1.8m) with 3.5mm stereo plugs
- IEC AC power cord
- Quick start guide



Local unit - rear view

Specification

Video

Maximum Resolution	1600x1280@60Hz up to 65m 1280x1024@75Hz up to 120m 1024x768@75Hz up to 300m
Video Compatibility	VGA to UXGA, RGB
Video I/O	0.7V P-P
VESA DDC	Local Unit emulates universal monitor. Custom DDC information can be supplied; contact Technical Support for details.
Video Compensation	Three stage continuously variable
Video Coupling	DC
Sync I/O	H/V or composite TTL level Sync polarity is preserved
Video In Connectors	HD15 (male)
Video Out Connectors	HD15 (female)

Keyboard and Mouse

KB Compatibility	PC/AT, PS/2
Mouse Compatibility	Standard PS/2 two/three button Standard wheel mice
Connectors (CPU)	6-pin miniDIN socket
Connectors (Device)	6-pin miniDIN socket

Serial Interface

Max Baud Rate	19.2k baud
Serial Data Format	Transparent
Signals Transferred	TX, RX, RTS, CTS, DTR,DSR
Local Connector	DB9 female (DCE)
Remote Connector	DB9 male (DTE)

Audio Interface

Description	Bi-directional stereo audio link
Transmission method	Digitized virtually CD quality audio (16-bit, 38.4kHz)
Signal levels	Line level (4V Pk-Pk maximum)
Input Impedance	47kΩ
Local Connectors	2x3.5mm stereo jack socket (Line In & Line Out)
Remote Connectors	2x3.5mm stereo jack socket (Line/Mic In & Line Out)
Microphone Support	May be connected to Remote Unit Pullup resistor provides bias for condenser microphone. Option to set microphone amplification to +17dB

Power Requirements

Local Unit	5V 200mA (max) supplied by PC's PS/2 keyboard port. External PS/2 PSU also available.
Remote Unit	9V DC, 0.75A (max) 2.5mm DC jack (centre positive)
Remote Unit PSU	9V DC, 2A (18W), isolated output (certified to all relevant safety standards) Universal IEC input 2.5mm DC jack (centre positive)

Size and Shipping Weight

Local Unit	202x100x44mm (1U)
Remote Unit	202x100x44mm (1U)
Shipping Weight	2.53 kg

Environmental

Operating Temp	0 to 40°C
Storage Temp	-30 to 65°C
Relative Humidity	5 - 90% non-condensing
Chassis Construction	Fully shielded. Black painted steel
Approvals	CE, FCC (Class A)

SDLink2/AU

Single Channel KVM Extender Kit

Application

